Z890 VALKYRIE Motherboard

- Supports Intel Core Ultra 9/7/5 Processor
- Intel Z890 single chip architecture
- Supports 4-DIMM DDR5 up to 256 GB Memory
- Supports PCIe 5.0 M.2
- Supports Display Port 2.1 & HDMI® 2.1
- Supports 5 GbE & 2.5 GbE LAN
- Supports USB 4 Type C
- Supports WiFi 7 module (No WiFi card included)

Specifcation

CPU SUPPORT	Support for Intel Core™ Ultra 9 / 7 / 5 processors in the LGA1851 package * Please refer to www.biostar.com.tw for CPU support list.
MEMORY	Supports Dual Channel DDR5 - 9066+(OC) MT/s, Non-ECC, Un-buffered ,Clocked Unbuffered DIMM (CUDIMM) Memory 4 x DDR5 DIMM Memory Slot, Max. Supports up to 256 GB Memory Support Intel® Extreme Memory Profile (XMP) memory modules * Please refer to www.biostar.com.tw for Memory support list.
INTEGRATED VIDEO	Supports DX12 Supports HDCP
STORAGE	Total supports 6 x M.2 socket and 4 x SATA III (6Gb/s) ports Intel Core Ultra Processors 1 x M.2 (M Key) Socket (M2M_CPU1): Supports M.2 Type 2280 SSD module Supports PCIe 5.0 x4 (128Gb/s) - NVMe SSD 1 x M.2 (M Key) Socket (M2M_CPU2): Supports M.2 Type 2280/22110 SSD module Supports PCIe 4.0 x4 (64Gb/s) - NVMe SSD Intel Z890 Chipset 1 x M.2 (M Key) Socket (M2M_SB1): Supports M.2 Type 2280 SSD module Supports PCIe 4.0 x4 (64Gb/s) - NVMe SSD 1 x M.2 (M Key) Socket (M2M_SB2): Supports M.2 Type 2280 SSD module Supports PCIe 4.0 x4 (64Gb/s) - NVMe SSD 1 x M.2 (M Key) Socket (M2M_SB3): Supports M.2 Type 2280 SSD module Supports PCIe 4.0 x4 (64Gb/s) - NVMe SSD 1 x M.2 (M Key) Socket (M2M_SB4): Supports M.2 Type 2280 SSD module Supports PCIe 4.0 x4 (64Gb/s) - NVMe SSD 4 x SATA III Connector (6Gb/s): Supports AHCI, RAID 0, 1, 5, 10 & Intel® Rapid Storage Technology

BIOSTAR
BIOSTAR Microtech International corp.

LAN	Realtek RTL8126 10/ 100/ 1000/ 2500/ 5000 Mb/s auto negotiation, Half / Full duplex capability Realtek RTL8125D 10/ 100/ 1000/ 2500 Mb/s auto negotiation, Half / Full duplex capability
AUDIO CODEC	Realtek ALC1220 7.1 Channels, High Definition Audio, Hi-Fi (front/rear)
USB	1 x USB 4.0 Type-C Port with (DP1.4) (1 on rear I/O) 1 x USB 3.2 (Gen2x2) Type-C port (1 via internal header) 11 x USB 3.2 (Gen2) port (9 on rear I/O and 2 via internal header) 4 x USB 2.0 Port (4 via interne Header)
EXPANSION SLOT	Intel Core Ultra Processors 1 x PCIe 5.0 x16 Slot (x16 mode or x8 mode) 1 x PCIe 5.0 x16 Slot (x8 mode or x4 mode) 1 x PCIe 5.0 x16 Slot (x4 mode)
REAR I/O	2 x WIFI Antenna Ports 2 x HDMI® Ports (HDMI®2.1) 1 x DP Port (DP2.1) 1 x USB 4.0 Type-C Port with (DP1.4) 9 x USB 3.2 (Gen2) Ports 1 x 5 Gigabit LAN port 1 x 2.5 Gigabit LAN port 2 x Audio Jack 1 x S/PDIF_Out 1 x SMART BIOS UPDATE Button 1 x SMART BIOS USB Port
INTERNAL I/O	4 x SATA III Connector (6Gb/s) 1 x M.2 (E Key) Socket : Supports 2230 type Wi-Fi & Bluetooth module and Intel GEN2 CNVi 1 x USB 3.2 (Gen2x2) Type-C Header (each header supports 1 USB 3.2 (Gen2x2) Type-C ports) 1 x USB 3.2 (Gen2) Header (each header supports 2 USB 3.2 (Gen2) ports) 2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 2 x 8-Pin Power Connector 1 x 24-Pin Power Connector 1 x CPU Fan Connector 1 x CPU water cooling connector (CPU_OPT) 4 x System Fan Connector 1 x Front Panel Header 1 x Front Audio Header 1 x Speaker Header 1 x Clear CMOS Button 1 x Power Switch Button 1 x Reset Switch Button 1 x COM Port Header 1 x TPM Header 1 x Thunderbolt Header 4 x LED Header (5V) 1 x LED Header (12V) 1 x IO_LED Header * M.2 (E Key) Wi-Fi card is not provided

PROSTAR
BIOSTAR Research International Corp.

RAID	Supports RAID 0, 1, 5, 10 for SATA storage devices Supports RAID 0, 1, 5, 10 for M.2 NVMe storage devices
H/W MONITORING	CPU / System Temperature Monitoring Smart / Manual CPU Fan Control CPU/DDR Voltage Monitoring
DIMENSION	ATX Form Factor Dimension: 24.4cm X 30.5cm (W x L)
OS SUPPORT	Supports Windows 10(64bit) / Windows 11(64bit) ※Biostar reserves the right to add or remove support for any OS with or without notice.
ACCESSORIES	4 x SATA Cable 1 x Quick Guide

OVERVIEW

Intel Z890 chipset

With the Intel® Z890 chipset and the Intel® Core™ Ultra 9/ 7/ 5 processors , you will immediately be at the forefront of the battlefield, fueled by mind-blowing power and performance. From content creation to gaming, the Intel Z890 chipset provides you with the power and performance you need.

HD Audio

Provides high quality sound with minimal loss of audio fidelity.

Hi-Fi Ground

BIOSTAR Hi-Fi Ground (Golden Line) is noise-blocking multi-layer PCB design to isolates analog audio signals from digital sources. Unique PCB layout is ideal for exceptional clarity and high fidelity sound.

Hi-Fi AMP

The built-in amplifier can drive major high-end headphones with over 100dB loads and offer wide band-width, low noise, high slew rate and low distortion audio source from front panel I/O. Gaming enthusiasts can enjoy a fuller range of dynamic sound with crisper details and less distortion.

Smart Ear

Smart EAR is a windows-based audio utility which allows you to easily adjust system volume. With its user-friendly GUI, you can also increase or decrease impedance setting (Low/High Gain) to optimize your headphone performance. You can easily enjoy high-quality and awesome sound.

DisplayPort

DisplayPort is a digital display interface developed by the Video Electronics Standards Association (VESA). The interface is primarily used to connect a video source to a display device such as a computer monitor, though it can also be used to carry audio.

BIOSTAR Micro Tech International Corp.

DX12

DirectX 12 introduces the next version of Direct3D, the graphics API at the heart of DirectX. Direct3D is one of the most critical pieces of a game or game engine, and we've redesigned it to be faster and more efficient than ever before. Direct3D 12 enables richer scenes, more objects, and full utilization of modern GPU hardware.

HDMI® 2.1

HDMI® 2.1 supports true 4K resolution- 4096*2160@120hz. A significant increase in bandwidth is up to 18mbps, and significant enhancements are added to support the continued increase consumer demands on video and audio experience.

SATAIII 6Gbps

SATAIII 6Gbps provides a higher bandwidth to retrieve and transfer HD media. With this super speed data transfer, SATAIII allows an incredible data boost which is 2x faster than the SATA II.

8-Layer Low-loss PCB Design

Providing stable power and higher energy efficiency , It is Able to offer the best overclocking experience.

DDR5

DDR5 provides 50% higher bandwidth than DDR4, the frequency can be up to 6000+(OC)MHz, and can boasts the largest memory capacity available. It also supports dual channels and has lower power consumption, which can provide better performance and experience for overclockers.

PCIe 5.0

PCIe 5.0 increases the data rate from 16GT/s to 32GT/s, which is twice as fast as PCIe 4.0. The maximum data transfer of bandwidth for two-way communication can reach 128GB/s. In addition, synchronized compatible with PCIe 4.0 and previous versions of devices.

PCIe 4.0 M.2

PCIe 4.0 M.2 delivers the highest bandwidth and lower latency. It is 2 times faster compared with PCIe 3.0 M.2 .

PCIe 5.0 M.2

PCIe 5.0 M.2 is the latest storage interface, it delivers the highest bandwidth and lower latency. It is 2 times faster compared with PCIe 4.0 M.2 .

USB 3.2 Gen2 Type-A

USB 3.2 Gen2 is a new standard called SuperSpeed USB 10Gbps to address increased performance and improve data transmission speed. It is for a max data transfer rate of 10Gbps and creates the best possible connection between your devices.

BIOSTAR
BIOSTAR Group International Corp.

USB 4.0 Type-C

The USB 4.0 supports a maximum transmission speed of 40Gbps, allowing for simultaneous data transfer and charging. It is also compatible with previous USB devices, making it the fastest and most convenient choice for users in terms of transmission interfaces.

Dr. MOS

Dr. MOS integrates driver ICs and high-side / low-side MOSFETs into a small package to reduce switching losses that enables superior efficiency and performance at higher switching frequencies.

USB 3.2 Gen2x2

USB 3.2 Gen2x2 is a new standard called SuperSpeed USB 20Gbps to address increased performance and improve data transmission speed. It is for a max data transfer rate of 20Gbps and creates the best possible connection between your devices.

Digital PWM

Digital PWM controller is with dual-output multiphase that faster transient performance and accurately regulated frequency control. It can be enabled to greatly increase system efficiency.

DUAL LAN

The DUAL LAN provides more options for network connectivity and the ability to isolate different network traffic, enhancing security. Additionally, in the event of one interface failure, a backup network interface is available, making it ideal for scenarios requiring high reliability and performance.

WiFi 7

The latest version of WiFi utilizes three different frequency bands: 2.4GHz, 5GHz, and 6GHz. It offers lower latency, improved performance, and enhanced security, allowing more devices to smoothly operate on wireless networks simultaneously under optimal conditions.

USB PD Charging

The USB PD Charging technology utilizes the USB Type-C interface, offering users a more convenient and efficient charging experience with faster charging speeds, intelligent power management, a single charging standard, and other advantages.

2.5 GbE LAN

The 2.5 GbE LAN offers faster transmission speeds compared to traditional 1 GbE LAN and is currently the mainstream transmission speed. It enhances data transmission speeds among devices within a local area network, making it particularly suitable for scenarios requiring large-scale data transfer.

5 GbE LAN

The speed of 5 GbE LAN is five times that of traditional 1 GbE LAN, offering higher transmission speeds suitable for applications requiring larger bandwidth, such as large file transfers, HD video streaming, virtualized environments, and more. Additionally, it is typically compatible with existing 1 GbE and 2.5 GbE devices, providing greater convenience.

ASROCK
Business Unit of Tech International Corp.

Tough Power Connectors

Tough Power Connectors are very robust that have larger area to ensure stable and reliable power supply. They can pack more power and durability to make your PC last longer.

Super Durable Inductor

Super Durable Inductor brings the benefits of higher current capacity, lower energy loss and better power stability.

Moistureproof PCB

The PCB will be oxidizing easily by damp or absorbed moisture, and ionic migration or CAF (Conductive Anodic Filament) will be generated. Moistureproof PCB meets high density and high reliability requirements for moisture proof.

ESD Protection

ESD (Electrostatic Discharge) is the major factor to destroy the PC by electrical overstress (EOS) condition. ESD occurred by PC users when touch any devices connect to a PC, which may result in damage to the motherboard or parts. ESD protection is designed to protect the motherboard and equipment from damage by EOS.

OC / OV / OH Protection

OC / OV / OH Protection design detects overvoltage conditions and prevents voltage surges from spreading in real time. It also actively cuts off the overvoltage supply to protect your system.

VIVID LED DJ

The VIVID LED DJ has launched a brand-new interface that offers better compatibility with peripheral devices, delivering the best lighting experience to users and allowing them to create a unique personal style.

UEFI BIOS

Unified Extensible Firmware Interface (UEFI) is a brand new framework that provides a revolutionary interface. It is a modern clear and easy-to-use graphical user interface. The UEFI comes with a colorful easy-understand icons leads users into the setup layer directly.

EZ Mode

BIOSTAR EZ Mode makes everything as simple and efficient as possible. It has an attractive easy-to-use BIOS system interface that guides users to solve their problems with ease. It lays out the things which you often do in BIOS system to make the flow smooth and seamless.

BIO-Flasher

BIO-Flasher is a convenient BIOS update tool. Just launch this tool and put the BIOS on USB pen driver before entering the OS. You can update your BIOS with only a few clicks without preparing an additional floppy disk or other complicated flash utility.

BIOSTAR
BIOSTAR Microtech International Corp.

Rapid Debug 3

Rapid Debug 3 posts critical POST code information in a digital LED display. When system malfunction occurs, it auto-detects the device's failure and translates the error codes on the digital LED.

A.I FAN

With A.I FAN users can ensure that their gaming PC can maintain its performance while staying cool. According to different cooling needs and usage scenarios, users can control speed modes. Allows users to have more customizability of fan modes and automatically detects different temperatures to make fan operate at defined speed for optimal cooling performance.

LED ROCK ZONE

LED ROCK ZONE comes with the RGB 12V LED header and Digital 5V LED header which offer more colorful lighting options to DIY lovers. Adjusting the color of LED and changing system colors by VIVID LED DJ will make you fully enjoy the process of PC modding developing your personal style.

CPU OPT

BIOSTAR offers one more fan header which is called CPU OPT. Users can use it to connect any kind of water coolers for a liquid cooling system. Keep your computer stable and enjoy your machine at the utmost potential.

BIOSTAR RGB SYNC

BISOTAR RGB SYNC is designed to create your personalized lighting effects. Let all the RGB peripherals and components sync together.

Smart Update

Biostar Smart Update is a utility that can help users run online update. It can download the drivers for your motherboard from Biostar official website and install them automatically.

SMART BIOS UPDATE

The easiest way to update the BIOS is provided.
Connect the USB driver to the SMART BIOS USB port to update.

EZ-Release

High-performance graphics cards often have bulkier dimensions, making their removal and installation somewhat inconvenient. However, with the EZ-Release, you can effortlessly remove your graphics card with just one click, eliminating the hassle of the removal process.

Auto Installer

The Auto Installer is capable of automatically installing the required drivers on Windows OS, providing users with a more intuitive and convenient experience, eliminating the hassle of manually searching for drivers.

BIOSTAR
BIOSTAR Microtech International Corp.

HDMI®

The terms HDMI® and HDMI® High-Definition Multimedia Interface, and the HDMI® Logo are trademarks or registered trademarks of HDMI® Licensing Administrator, Inc. in the United States and other countries.

*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!

BIOSTAR
BIOSTAR Microtech International corp.