
BIOSTAR
WWW.BIOSTAR.COM.TW

TForce4 SLI Motherboard



- Socket 939
- Supports AMD Athlon 64 X2/64/FX/Sempron Processors
- Hyper Transport Technology up to 2G
- Supports AMD Cool'nQuiet Technology
- Supports BIO-Remote 2 Technology
- Supports Charger Booster Technology

TForce4 SLI Specifcation

MEMORY	Support Dual Channel DDR 333/400 MHz 4 x DDR DIMM Memory Slot Max. Supports up to 4GB Memory
LAN	NVIDIA Gigabit MAC + VITESSE VSC8201 - 10/100/1000 PHY
AUDIO CODEC	Realtek ALC850 8-Channel AC97 Audio
EXPANSION SLOT	2 x PCI-E x16 Slot (SLI x8) 2 x PCI-E x1 Slot 3 x PCI Slot
REAR I/O	1 x PS/2 Mouse 1 x PS/2 Keyboard 1 x FireWire IEEE 1394a Port 4 x USB 2.0 Port 1 x COM Port 1 x Printer Port 1 x LAN Port 6 x Audio Jacks

BIOSTAR

INTERNAL I/O	3 x USB 2.0 Header 4 x SATA II Connector (3Gb/s) 2 x IDE Connector 1 x Floppy Connector 1 x Front Audio Header 1 x CD-IN Header 1 x S/PDIF-Out Header 1 x CPU Fan Connector 1 x System Fan Connector
DIMENSION	ATX Form Factor Dimension: 23.4 cm x 29.35 cm (W x L)
OS SUPPORT	Supports Windows 2000 / WinXP / WinXP 64
ACCESSORIES	2 x IDE Cable 1 x FDD Cable 4 x SATA Cable 1 x SATA Power Cable 1 x S/PDIF Cable 1 x I/O Shield 1 x Ear Phone 1 x USB Charge Set 1 x Fully Setup Driver CD 1 x User Manual 1 x Package Bag
FEATURES	Supports Solid capacitor Supports O.N.E Supports C.R.P Supports S.R.S Supports M.I.T Supports T-Power Supports Rapid Switch Supports Rapid Debug

TForce4 SLI OVERVIEW

*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!

BIOSTAR