


N68S3B Motherboard



- Socket AM3
- Supports AMD Phenom II/Athlon II/Sempron Processors
- Hyper Transport Technology up to 2G
- Supports AMD Cool'n'Quiet Technology
- It is recommended to use 95w CPU
- Supports BIO-Remote 2 Technology
- Supports Charger Booster Technology

N68S3B Specification

CPU SUPPORT	AMD Phenom™ II X4 Processor AMD Phenom™ II X3 Processor AMD Phenom™ II X2 Processor AMD Athlon™ II X4 Processor AMD Athlon™ II X3 Processor AMD Athlon™ II X2 Processor AMD Sempron™ Processor Maximum CPU TDP (Thermal Design Power) : 95Watt
HT	Support HT 2G
MEMORY	Support Dual Channel DDR3 800/1066/1333(supported by CPU model) MHz 2 x DDR3 DIMM Memory Slot Max. Supports up to 8GB Memory
INTEGRATED VIDEO	NVIDIA GeForce 7025 GPU, On Board Graphic Max. Memory Share Up to 512MB(Under OS By Turbo Cache)
STORAGE	2 x SATA II Connector 1 x IDE Connector Support SATA RAID: 0,1
LAN	Realtek RTL8201CL - 10/100 PHY
AUDIO CODEC	VIA VT1708B 6-Channel HD Audio

USB	4 x USB 2.0 Port 2 x USB 2.0 Header
EXPANSION SLOT	1 x PCI-E x16 Slot 1 x PCI Slot
REAR I/O	1 x PS/2 Mouse 1 x PS/2 Keyboard 4 x USB 2.0 Port 1 x VGA Port 1 x LAN Port 3 x Audio Jacks
INTERNAL I/O	2 x USB 2.0 Header 2 x SATA II Connector (3Gb/s) 1 x IDE Connector 1 x Front Audio Header 1 x Front Panel Header 1 x CPU Fan Connector 1 x System Fan Connector 1 x Printer Port Header
DIMENSION	Micro ATX Form Factor Dimension: 23.5cm x 17cm (W x L)
OS SUPPORT	Supports Windows XP / Vista / 7
ACCESSORIES	2 x SATA Cable 1 x I/O Shield 1 x Fully Setup Driver CD 1 x Quick Guide
FEATURES	Windows 7 Compatible Supports AM3 Supports Solid capacitor BIO-FLASHER

N68S3B OVERVIEW

***The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!**