


P4TDH Motherboard



-
- Supports BIO-Remote 2 Technology
- Supports Charger Booster Technology

P4TDH Specification

FSB	Support FSB 533MHz
MEMORY	Support DDR 266 MHz 3 x DDR DIMM Memory Slot Max. Supports up to 2GB Memory
INTEGRATED VIDEO	Intel Extreme Graphics 2 , On Board Graphic Max. Share Memory Up To 64MB
STORAGE	4 x IDE Connector
AUDIO CODEC	C-Media CMI8738 6-Channel AC97 Audio
USB	2 x USB 2.0 Port 2 x USB 2.0 Header
EXPANSION SLOT	5 x PCI Slot 1 x CNR Slots 1 x AGP X Slot
REAR I/O	1 x PS/2 Mouse 1 x PS/2 Keyboard 2 x USB 2.0 Port 2 x COM Port 1 x Printer Port 3 x Audio Jacks

INTERNAL I/O	2 x USB 2.0 Header 4 x IDE Connector 1 x Floppy Connector 1 x IrDA Header 1 x Front Audio Header
DIMENSION	ATX Form Factor Dimension: 24.4cm X 30.5cm (W x L)

P4TDH OVERVIEW

*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!

BIOSTAR