

# H310MHG Motherboard



- Supports 8th & 9th Generation Intel® Core™ Processor
- Intel H310 single chip architecture
- Support Dual Channel DDR4 2666/2400/2133/1866 MHz
- Support HDMI® 4K resolution
- Support GbE LAN
- Support USB 3.2 Gen1

## Specification

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CPU SUPPORT      | 9th Gen Intel® Core™ i9 LGA 1151 Processor<br>9th Gen Intel® Core™ i5 LGA 1151 Processor<br>9th Gen Intel® Core™ i3 LGA 1151 Processor<br>8th Gen Intel® Core™ i7 LGA 1151 Processor<br>8th Gen Intel® Core™ i5 LGA 1151 Processor<br>8th Gen Intel® Core™ i3 LGA 1151 Processor<br>8th Gen Intel® Pentium® LGA 1151 Processor<br>8th Gen Intel® Celeron® LGA 1151 Processor<br>Maximum CPU TDP (Thermal Design Power) : 95Watt<br>* Please refer to <a href="http://www.biostar.com.tw">www.biostar.com.tw</a> for CPU support list. |
| MEMORY           | Support Dual Channel DDR4 2666/ 2400/ 2133/ 1866 MHz<br>2 x DDR4 DIMM Memory Slot<br>Max. Supports up to 32GB Memory                                                                                                                                                                                                                                                                                                                                                                                                                  |
| INTEGRATED VIDEO | Supports DX12<br>Supports HDCP                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| STORAGE          | 4 x SATA III Connectors (6Gb/s)<br>1 x M.2 (M Key) Connector(10Gb/s) : Supports PCI-E (10Gb/s) & SATA III (6Gb/s)SSD                                                                                                                                                                                                                                                                                                                                                                                                                  |
| LAN              | Realtek RTL8111H - 10/100/1000Mb/s Controller                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| AUDIO CODEC      | Realtek ALC887 7.1-Channel HD Audio<br>Support HD Audio                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| USB              | 4 x USB 3.2 Gen1 Port (2 on rear I/Os and 2 via internal header)<br>6 x USB 2.0 Port (4 on rear I/Os and 2 via internal header)                                                                                                                                                                                                                                                                                                                                                                                                       |
| EXPANSION SLOT   | 1 x PCI-E 3.0 x16 Slot<br>2 x PCI-E 2.0 x1 Slot<br>1 x PCI Slot                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REAR I/O        | 1 x PS/2 Mouse<br>1 x PS/2 Keyboard<br>2 x USB 3.2 Gen1 Ports<br>4 x USB 2.0 Port<br>1 x COM Port<br>1 x HDMI® Connector<br>1 x DVI-D Connector<br>1 x VGA Port<br>1 x LAN Port<br>3 x Audio Jacks                                                                                                                                                                                                                                                                     |
| INTERNAL I/O    | 1 x USB 3.2 Gen1 Header (each header supports 2 USB 3.2(Gen1) ports)<br>1 x USB 2.0 Header (each header supports 2 USB 2.0 ports)<br>4 x SATA III Connector (6Gb/s)<br>1 x Front Audio Header<br>1 x Front Panel Header<br>1 x CPU Fan Connector<br>2 x System Fan Connector<br>1 x Chassis Instruction Header<br>1 x TPM Header<br>1 x 8-Pin Power Connector<br>1 x 24-Pin Power Connector<br>1 x Clear CMOS Header<br>1 x COM Port Header<br>1 x Printer Port Header |
| H/W MONITORING  | CPU / System Temperature Monitoring<br>CPU / System Fan Monitoring<br>Smart / Manual CPU Fan Control<br>CPU/DDR Voltage Monitoring                                                                                                                                                                                                                                                                                                                                     |
| DIMENSION       | Micro ATX Form Factor Dimension: 24.4cm x 18.8cm ( W x L )                                                                                                                                                                                                                                                                                                                                                                                                             |
| OS SUPPORT      | Supports Windows 11(64bit) / 10(64bit)<br>Windows 7<br>※* BIOSTAR reserves the right to add or remove support for any OS with or without notice.                                                                                                                                                                                                                                                                                                                       |
| BUNDLE SOFTWARE | BullGuard                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| ACCESSORIES     | 2 x SATA Cable<br>1 x I/O Shield<br>1 x Fully Setup Driver CD<br>1 x Quick Guide                                                                                                                                                                                                                                                                                                                                                                                       |
| FEATURES        | BIO-FLASHER                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## OVERVIEW



### Intel H310 chipset

The Intel® H310 chipset is a single-chipset design to support socket 1151 Intel® 8th generation Intel® Core™ processor-based platform. Provides excellent performance and increased bandwidth and stability. The PC platform features improved adaptive performance that adds speed when you need it. When combined with advanced system responsiveness, the platform delivers the ultimate PC experience.

|                                                                                     |                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|     | <h3>DVI</h3> <p>DVI is better than VGA for LCD displays since it is digital while VGA is analog. For LCD displays, the picture is digitized pixel per pixel. Through DVI, the panel gets data for each pixel, so the picture generated in the Graphics device matches the pixels on the panel itself.</p>                                                        |
|    | <h3>DX12</h3> <p>DirectX 12 introduces the next version of Direct3D, the graphics API at the heart of DirectX. Direct3D is one of the most critical pieces of a game or game engine, and we've redesigned it to be faster and more efficient than ever before. Direct3D 12 enables richer scenes, more objects, and full utilization of modern GPU hardware.</p> |
|    | <h3>Integrated HDMI® with HDCP</h3> <p>Onboard HDMI® connector allows full video &amp; audio support. It has industry-leading high definition video quality.</p>                                                                                                                                                                                                 |
|    | <h3>PCIe M.2 (10Gb/s)</h3> <p>it delivers faster performance compared with SATA interface 6Gb/s.</p>                                                                                                                                                                                                                                                             |
|   | <h3>PCIe 3.0</h3> <p>PCIe 3.0 is the ubiquitous and general-purpose PCI Express I/O standard. At 8GT/s bit rate, the interconnect performance bandwidth is doubled over PCIe 2.0, while preserving compatibility with software and mechanical interfaces.</p>                                                                                                    |
|  | <h3>SATAIII 6Gbps</h3> <p>SATAIII 6Gbps provides a higher bandwidth to retrieve and transfer HD media. With this super speed data transfer, SATAIII allows an incredible data boost which is 2x faster than the SATA II.</p>                                                                                                                                     |
|  | <h3>USB 3.2 Gen1 Type-A</h3> <p>USB 3.2 Gen1 delivers a compelling performance boosts and can be used to connect multiple devices without worrying about compatibility. It is capable of data transfer speeds up to 5Gbps and backwards compatible with all existing USB products.</p>                                                                           |
|  | <h3>100% Solid Caps</h3> <p>With armor-plated Biostar Technology, all capacitors are placed with 100% solid capacitors that have a lasting life cycle, durability and stability for crucial components.</p>                                                                                                                                                      |
|  | <h3>UEFI BIOS</h3> <p>Unified Extensible Firmware Interface (UEFI) is a brand new framework that provides a revolutionary interface. It is a modern clear and easy-to-use graphical user interface. The UEFI comes with a colorful easy-understand icons leads users into the setup layer directly.</p>                                                          |
|  | <h3>HDMI®</h3> <p>The terms HDMI® and HDMI® High-Definition Multimedia Interface, and the HDMI® Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.</p>                                                                                                                                 |

\*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!



BIOSTAR  
BIOSTAR Microtech International Corp.

