BIOSTAR
WWW.BIOSTAR.COM.TW

TF680i SLI Deluxe Motherboard



- Socket LGA 775
- Supports Intel Core 2 Extreme/Core 2 Quad/Core 2 Duo/Pentium D/Pentium 4/Celeron D Processor
- Supports FSB 1333MHz
- Support Intel Hyper-Threading Technology
- Supports BIO-Remote 2 Technology
- Supports Charger Booster Technology

TF680i SLI Deluxe Specifcation

MEMORY	Support Dual Channel DDR2 533/667/800 MHz 4 x DDR2 DIMM Memory Slot Max. Supports up to 8GB Memory
LAN	Marrvell 88E1116 - 10/100/1000 PHY
AUDIO CODEC	Realtek ALC885 8-Channel HD Audio
EXPANSION SLOT	1 x PCI-E x16 Slot 2 x PCI-E x16 Slot (SLI x16) 2 x PCI-E x1 Slot 2 x PCI Slot
REAR I/O	1 x PS/2 Mouse 1 x PS/2 Keyboard 2 x FireWire IEEE 1394a Port 6 x USB 2.0 Port 1 x COM Port 2 x LAN Port 6 x Audio Jacks

BIOSTAR

INTERNAL I/O	2 x USB 2.0 Header 6 x SATA II Connector (3Gb/s) 1 x IDE Connector 1 x Floppy Connector 1 x Front Audio Header 1 x Front Panel Header 1 x S/PDIF-Out Header 1 x CPU Fan Connector 3 x System Fan Connector 1 x Chassis Instruction Header
DIMENSION	ATX Form Factor Dimension: 23.4 cm x 29.35 cm (W x L)
OS SUPPORT	Supports Windows 2000 / WinXP / WinXP 64 / Vista
ACCESSORIES	1 x IDE Cable 1 x FDD Cable 4 x SATA Cable 4 x SATA Power Cable 1 x SLI Connector 1 x I/O Shield 2 x Memory Heatsink 1 x Fully Setup Driver CD 1 x User Manual 1 x Package Bag
FEATURES	Supports Solid capacitor Supports Fanless

TF680i SLI Deluxe OVERVIEW

*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!

POSTAR