
BIOSTAR
WWW.BIOSTAR.COM.TW

GF7100P-M7S Motherboard



- Socket LGA 775
- Supports Intel Core 2 Quad/Core 2 Duo/Pentium D/Pentium 4/Celeron 400 Series/Celeron D Processor(and 45nm CPU)
- Supports FSB 800/1066/1333MHz
- Supports BIO-Remote 2 Technology
- Supports Charger Booster Technology

GF7100P-M7S Specifcation

CPU SUPPORT	Intel® Core™2 Quad Processor Intel® Core™2 Duo Processor Intel® Pentium® Dual-Core Processor Intel® Pentium® D Processor Intel® Pentium® 4 Processor Intel® Celeron® D Processor Intel® Celeron® Processor 400 Sequence
FSB	Support FSB 800/1066/1333MHz
MEMORY	Support DDR2 533/667/800 MHz 2 x DDR2 DIMM Memory Slot Max. Supports up to 4GB Memory
INTEGRATED VIDEO	NVIDIA GeForce 7100P GPU, On Board Graphic Max. Memory Share Up to 512MB(Under OS By Turbo Cache)),GPU Frequency @600MHz
STORAGE	4 x SATA II Connector 1 x IDE Connector Support SATA RAID: 0,,1,5,0+1
LAN	Realtek RTL8111B - 10/100/1000 Controller

BIOSTAR

AUDIO CODEC	Realtek ALC662 6-Channel HD Audio
USB	4 x USB 2.0 Port 3 x USB 2.0 Header
EXPANSION SLOT	1 x PCI-E x16 Slot 1 x PCI-E x1 Slot 2 x PCI Slot
REAR I/O	1 x PS/2 Keyboard 4 x USB 2.0 Port 1 x DVI Connector 1 x VGA Port 1 x LAN Port 3 x Audio Jacks
INTERNAL I/O	3 x USB 2.0 Header 4 x SATA II Connector (3Gb/s) 1 x IDE Connector 1 x Floppy Connector 1 x Front Audio Header 1 x Front Panel Header 1 x CD-IN Header 1 x S/PDIF-Out Header 1 x CPU Fan Connector 1 x North Bridge FAN Header 1 x System Fan Connector 1 x COM Port Header 1 x Printer Port Header
DIMENSION	Micro ATX Form Factor Dimension: 24.4 cm X 24.4cm (W x L)
OS SUPPORT	Supports Windows XP / Vista
ACCESSORIES	1 x IDE Cable 1 x FDD Cable 1 x SATA Cable 1 x I/O Shield 1 x Fully Setup Driver CD 1 x User Manual

GF7100P-M7S OVERVIEW

*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!

BIOSTAR