
BIOSTAR
WWW.BIOSTAR.COM.TW

G31M Motherboard



- Socket LGA 775
- Supports Intel Core 2 Duo/ Pentium Dual-Core/ Pentium 4/ Celeron Dual-Core/ Celeron 400 Series Processor
- Supports FSB 800/1066/1333MHz
- Support Intel Hyper-Threading Technology
- Supports BIO-Remote 2 Technology

G31M Specifcation

CPU SUPPORT	Intel® Core™2 Duo Processor Intel® Pentium® Dual-Core Processor Intel® Pentium® 4 Processor Intel® Celeron® Dual-Core Processor Intel® Celeron® Processor 400 Sequence Maximum CPU TDP (Thermal Design Power) : 65Watt
FSB	Support FSB 533/800/1066/1333MHz FSB533 CPU only support DDR2-533
MEMORY	Support Dual Channel DDR2 533/667/800 MHz 2 x DDR2 DIMM Memory Slot Max. Supports up to 4GB Memory DDR2-533 for FSB533 / FSB1066 CPU only
INTEGRATED VIDEO	Intel Graphics Media Accelerator 3100 On Board Graphic Max. Share Memory 384MB
STORAGE	2 x SATA II Connector 1 x IDE Connector
LAN	Realtek RTL8103EL - 10/100 Controller
AUDIO CODEC	VIA VT1708B 6-Channel HD Audio

BIOSTAR

USB	4 x USB 2.0 Port 2 x USB 2.0 Header
EXPANSION SLOT	1 x PCI-E x16 Slot 1 x PCI Slot
REAR I/O	1 x PS/2 Mouse 1 x PS/2 Keyboard 4 x USB 2.0 Port 1 x VGA Port 1 x LAN Port 3 x Audio Jacks
INTERNAL I/O	2 x USB 2.0 Header 2 x SATA II Connector (3Gb/s) 1 x IDE Connector 1 x Floppy Connector 1 x Front Audio Header 1 x Front Panel Header 1 x CPU Fan Connector 1 x System Fan Connector 1 x Printer Port Header
DIMENSION	Micro ATX Form Factor Dimension: 22.5 cm X 17 cm (W x L)
OS SUPPORT	Supports Windows XP / Vista / 7
ACCESSORIES	2 x SATA Cable 1 x I/O Shield 1 x Fully Setup Driver CD 1 x User Manual
FEATURES	Supports Solid capacitor BIO-FLASHER

G31M OVERVIEW

*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!

BIOSTAR