

## P4M800 Pro-M7 Combo Motherboard



- Socket LGA 775
- Supports Intel Pentium 4/Celeron D Processor
- Supports FSB 1066MHz
- Support Intel Hyper-Threading Technology
- Supports BIO-Remote 2 Technology
- Supports Charger Booster Technology

## P4M800 Pro-M7 Combo Specification

|                  |  |
|------------------|--|
| MEMORY           | Support DDR2 400/533 MHz<br>2 x DDR2 DIMM Memory Slot<br>Max. Supports up to 2GB Memory  |
| INTEGRATED VIDEO | VIA S3 UniChrome, On Board Graphic Max. Memory Share Up to 64MB  |
| LAN              | Realtek RTL8201CL - 10/100 PHY   |
| AUDIO CODEC      | Realtek ALC655 6-Channel AC97 Audio  |
| EXPANSION SLOT   | 3 x PCI Slot<br>1 x CNR Slots<br>1 x AGP 8X Slot   |
| REAR I/O         | 1 x PS/2 Mouse<br>1 x PS/2 Keyboard<br>4 x USB 2.0 Port<br>1 x COM Port<br>1 x Printer Port<br>1 x VGA Port<br>1 x LAN Port<br>3 x Audio Jacks               |
| INTERNAL I/O     | 2 x USB 2.0 Header<br>2 x SATA Connector<br>2 x IDE Connector<br>1 x Floppy Connector<br>1 x Front Audio Header<br>1 x CD-IN Header<br>1 x S/PDIF-Out Header |

|             |  |
|-------------|--|
| DIMENSION   | Micro ATX Form Factor Dimension: 24.38cm x 20.17cm ( W x L )   |
| OS SUPPORT  | Supports Windows 2000 / XP   |
| ACCESSORIES | 1 x IDE Cable<br>1 x FDD Cable (Optional)<br>1 x SATA Cable (Optional)<br>1 x I/O Shield<br>1 x Fully Setup Driver CD<br>1 x User Manual |

## P4M800 Pro-M7 Combo OVERVIEW

\*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!

BIOSTAR