H410MH S2 Motherboard

- Supports 10th Generation Intel Core™ Processor
- Intel H510 single chip architecture
- Supports 2-DIMM DDR4- 2933/ 2666/ 2400/2133/ 1866 up to 64 GB Memory
- Supports PCIe 3.0
- Supports PCIe M.2 (32Gb/s)
- Supports USB 3.2 Gen1

Specifcation	
CPU SUPPORT	Socket 1200 for 10th Gen Intel Core™, Pentium and Celeron processors * Please refer to www.biostar.com.tw for CPU support list.
MEMORY	Supports Dual Channel DDR4 1866/ 2133/ 2400/ 2666/ 2800/ 2933 2 x DDR4 DIMM Memory Slots, Max. Supports up to 64 GB Memory Each DIMM supports non-ECC 4/8/16/32GB DDR4 module * Please refer to Memory Support List for more information. Core (i9/i7) support DDR4 up to 2933 MHz; Core (i5/i3), Pentium and Celeron support DDR4 up to 2666 MHz.
INTEGRATED VIDEO	Supports DX12 Supports HDCP
STORAGE	4 x SATA III Connector (6Gb/s) 1 x M.2 (M Key) Socket: Supports M.2 Type 2242/ 2260/ 2280 SSD module. Supports PCIe 3.0 x 4 (32Gb/s) & SATA III (6Gb/s) SSD * When using SATA SSD module on PCIE-M2_1 slot, the SATA_1 connector will be disabled.
LAN	Intel I219V 10/ 100/ 1000 Mb/s auto negotiation, Half / Full duplex capability
AUDIO CODEC	Realtek ALC887 7.1 Channels, High Definition Audio
USB	4 x USB 3.2(Gen1) ports (2 on rear I/Os and 2 via internal headers) 6 x USB 2.0 ports (4 on rear I/Os and 2 via internal headers)
EXPANSION SLOT	2 x PCIe 3.0 x 1 Slots 1 x PCIe 3.0 x 16 Slot

BIOSTAR
BIOSTAR Microtech International corp.

REAR I/O	1 x PS/2 Keyboard 1 x PS/2 Mouse 1 x HDMI® Port 1 x VGA Port 2 x USB 3.2 (Gen1) Ports 4 x USB 2.0 Ports 1 x LAN port 3 x Audio Jack
INTERNAL I/O	4 x SATA III Connectors (6Gb/s) 1 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports) 1 x 8-Pin Power Connector 1 x 24-Pin Power Connector 1 x CPU Fan Connector 1 x System Fan Connector 1 x Front Panel Header 1 x Front Audio Header 1 x Clear CMOS Header 1 x COM Port Header
H/W MONITORING	CPU / System Temperature Monitoring CPU / System Fan Monitoring Smart / Manual CPU Fan Control CPU/DDR Voltage Monitoring
DIMENSION	Micro ATX Form Factor Dimension: 18.5cm x 22.6cm (W x L)
OS SUPPORT	Supports Windows 10 (64bit) / 11(64bit) ※Biostar reserves the right to add or remove support for any OS with or without notice.
BUNDLE SOFTWARE	BullGuard
ACCESSORIES	2 x SATA Cable 1 x I/O Shield 1 x DVD Driver 1 x Quick Guide
FEATURES	Supports 100% Solid capacitor

OVERVIEW

Intel H510 chipset

With the Intel® H510 chipset and the 10th/ 11th generation Intel® Core™ i9/ i7/ i5/ i3 processors and Intel® Pentium® processors, you will immediately be at the forefront of the battlefield, fueled by mind-blowing power and performance. From content creation to gaming, the Intel H510 chipset provides you with the power and performance you need.

HD Audio

Provides high quality sound with minimal loss of audio fidelity.

BIOSTAR
BIOSTAR Microtech International Corp.

HDMI® 4K2K

The new 4K2K resolution enables high-definition image display with four times the resolution of full HD, 4K2K display is faithfully express bright, highly detailed content that fills the entire screen with lifelike images. Connectivity with PCs via a single HDMI® cable for displaying 4K2K data.

DX12

DirectX 12 introduces the next version of Direct3D, the graphics API at the heart of DirectX. Direct3D is one of the most critical pieces of a game or game engine, and we've redesigned it to be faster and more efficient than ever before. Direct3D 12 enables richer scenes, more objects, and full utilization of modern GPU hardware.

Integrated HDMI® with HDCP

Onboard HDMI® connector allows full video & audio support. It has industry-leading high definition video quality.

Intel GbE LAN

Unlike ordinary LAN solution, Intel® GbE LAN offers fewer CPU resource consumption and more bandwidth stability. Thus, Intel® LAN is the best choice for performance seekers.

PCIe M.2 (10Gb/s)

it delivers faster performance compared with SATA interface 6Gb/s.

PCIe 3.0

PCIe 3.0 is the ubiquitous and general-purpose PCI Express I/O standard. At 8GT/s bit rate, the interconnect performance bandwidth is doubled over PCIe 2.0, while preserving compatibility with software and mechanical interfaces.

SATAIII 6Gbps

SATAIII 6Gbps provides a higher bandwidth to retrieve and transfer HD media. With this super speed data transfer, SATAIII allows an incredible data boost which is 2x faster than the SATA II.

Dual DDR4

The primary advantages of DDR4 over DDR3, include higher module density, lower voltage requirements, coupled with higher data transfer rate.

USB 3.2 Gen1 Type-A

USB 3.2 Gen1 delivers a compelling performance boosts and can be used to connect multiple devices without worrying about compatibility. It is capable of data transfer speeds up to 5Gbps and backwards compatible with all existing USB products.

5 Phase Power Phase Design

5-phase VRM design with high quality power components such as low RDS (on) Mosfet for lower temperature has the advantage to raise the overclocking ability.

BIOSTAR
BIOSTAR Microtech International Corp.

100% Solid Caps

With armor-plated Biostar Technology, all capacitors are placed with 100% solid capacitors that have a lasting life cycle, durability and stability for crucial components.

BullGuard Internet Security (90 days FREE trial)

BullGuard Internet Security comes with the broadest line-up of internet security features on the market, including: a cutting-edge dual Antivirus engine, Online Backup for your precious files, PC Tune Up to speed up your system, a Game Mode for a seamless gaming experience, Parental Control, Firewall, Safe Browsing and many more. Make the most of your digital life with Bullguard!

UEFI BIOS

Unified Extensible Firmware Interface (UEFI) is a brand new framework that provides a revolutionary interface. It is a modern clear and easy-to-use graphical user interface. The UEFI comes with a colorful easy-understand icons leads users into the setup layer directly.

BIO-Flasher

BIO-Flasher is a convenient BIOS update tool. Just launch this tool and put the BIOS on USB pen driver before entering the OS. You can update your BIOS with only a few clicks without preparing an additional floppy disk or other complicated flash utility.

HDMI®

The terms HDMI® and HDMI® High-Definition Multimedia Interface, and the HDMI® Logo are trademarks or registered trademarks of HDMI® Licensing Administrator, Inc. in the United States and other countries.

*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!

BIOSTAR
BIOSTAR Microtech International corp.