

# B850MT-E PRO Motherboard



- Supports AMD Ryzen™ 9000 / 8000 / 7000 series Processors
- AMD B850 single chip architecture
- Supports 4-DIMM DDR5 up to 256 GB Memory
- Supports PCIe 5.0 M.2
- Supports HDMI® & Display Port
- Supports 2.5 GbE LAN
- Supports USB 3.2 Gen2 Type C
- Supports WiFi 7 & 6E module (No WiFi card included)

## Specification

|                  |  |
|------------------|--|
| CPU SUPPORT      | Socket AM5 support AMD Ryzen™ 9000 / 8000 / 7000 series Processors<br>Support for future AMD Ryzen processors with BIOS update<br>* Please refer to <a href="http://www.biostar.com.tw">www.biostar.com.tw</a> for CPU support list.   |
| MEMORY           | AMD Ryzen 9000 / 8000 / 7000 Series Processors:<br>Supports Dual Channel DDR5 - 8000+(OC) MT/s, Non-ECC, Un-buffered Memory<br>4 x DDR5 DIMM Memory Slot, Max. Supports up to 256 GB Memory<br>Support Intel® Extreme Memory Profile (XMP) memory modules and AMD<br>EXTended Profiles for Overclocking (EXPO) memory modules<br>* Please refer to <a href="http://www.biostar.com.tw">www.biostar.com.tw</a> for Memory support list. |
| INTEGRATED VIDEO | By CPU model<br>Supports DX12<br>Supports HDCP   |





BIOSTAR  
 Tech International Corp.

|                |   |
|----------------|---|
| STORAGE        | <p>Total support 3 x M.2 Socket and 2 x SATA (6Gb/s) ports<br/> AMD Ryzen 9000 / 8000 / 7000 Series Processors<br/> 1 x M.2 (Key M) Socket (M2M_CPU1):<br/> Supports M.2 Type 2280 SSD module<br/> Supports PCIe 5.0 x4 (128Gb/s) - NVMe SSD (AMD Ryzen 9000 / 7000 Series Processor)<br/> Supports PCIe 4.0 x4 (64Gb/s) - NVMe SSD (AMD Ryzen 8000 Series - Phoenix1 Processor)<br/> Supports PCIe 4.0 x4 (64Gb/s) - NVMe SSD (AMD Ryzen 8000 Series - Phoenix2 Processor)<br/> 1 x M.2 (Key M) Socket (M2M_CPU2):<br/> Supports M.2 Type 2280 SSD module<br/> Supports PCIe 5.0 x4 (128Gb/s) - NVMe SSD (AMD Ryzen 9000 / 7000 Series Processor)<br/> Supports PCIe 4.0 x4 (64Gb/s) - NVMe SSD (AMD Ryzen 8000 Series - Phoenix1 Processor)<br/> Supports PCIe 4.0 x2 (32Gb/s) - NVMe SSD (AMD Ryzen 8000 Series - Phoenix2 Processor)<br/> AMD B850 Chipset<br/> 1 x M.2 (Key M) Socket (M2M_SB):<br/> Support M.2 Type 2280 SSD module<br/> Support PCIe 4.0 x4 (64Gb/s) - NVMe SSD<br/> 2 x SATA III Connector (6Gb/s):<br/> Supports AHCI &amp; RAID 0, 1</p> |
| LAN            | <p>Realtek RTL8125D<br/> 10/ 100/ 1000/ 2500 Mb/s auto negotiation, Half / Full duplex capability</p>   |
| AUDIO CODEC    | <p>Realtek ALC897<br/> 7.1 Channels, High Definition Audio</p>  |
| USB            | <p>2 x USB 3.2 (Gen2) Type-C ports<br/> (1 on rear I/O and 1 via internal header)<br/> 1 x USB 3.2 (Gen2) port<br/> (1 on rear I/O)<br/> 6 x USB 3.2 (Gen1) ports<br/> (4 on rear I/O and 2 via internal header)<br/> 6 x USB 2.0 ports<br/> (2 on rear I/O and 4 via internal header)</p>  |
| EXPANSION SLOT | <p>AMD Ryzen 9000 / 8000 / 7000 Series Processors<br/> (PCIEX16_1):<br/> Supports 1 x PCIe 5.0 x16 Slot (x16 mode) (AMD Ryzen 9000 / 7000 Series Processor)<br/> Supports 1 x PCIe 4.0 x16 Slot (x8 mode) (AMD Ryzen 8000 Series - Phoenix1 Processor)<br/> Supports 1 x PCIe 4.0 x16 Slot (x4 mode) (AMD Ryzen 8000 Series - Phoenix2 Processor)<br/> (PCIEX16_2):<br/> Supports 1 x PCIe 4.0 x16 Slot (x4 mode)</p>   |
| REAR I/O       | <p>2 x WiFi Antenna Ports<br/> 1 x HDMI® Port<br/> 1 x DP Port (DP1.2)<br/> 1 x USB 3.2 (Gen2) Type-C Port<br/> 1 x USB 3.2 (Gen2) Port<br/> 4 x USB 3.2 (Gen1) Port<br/> 2 x USB 2.0 Ports<br/> 1 x 2.5 Gigabit LAN port<br/> 3 x Audio Jack<br/> 1 x SMART BIOS UPDATE Button<br/> 1 x SMART BIOS USB Port</p>  |

|              |   |
|--------------|---|
| INTERNAL I/O | <p>2 x SATA III Connector (6Gb/s)</p> <p>1 x M.2 (E Key) Socket : Supports 2230 type Wi-Fi &amp; Bluetooth module</p> <p>1 x USB 3.2 (Gen2) Type-C Port<br/>(each header supports 1 USB 3.2 (Gen2) Type-C port)</p> <p>1 x USB 3.2 (Gen1) Header<br/>(each header supports 2 USB 3.2 (Gen1) ports)</p> <p>2 x USB 2.0 Header<br/>(each header supports 2 USB 2.0 ports)</p> <p>1 x 8-Pin Power Connector</p> <p>1 x 24-Pin Power Connector</p> <p>1 x CPU Fan Connector</p> <p>1 x CPU water cooling connector (CPU_OPT)</p> <p>2 x System Fan Connector</p> <p>1 x Front Panel Header</p> <p>1 x Front Audio Header</p> <p>1 x Speaker Header</p> <p>1 x Clear CMOS Header</p> <p>1 x COM Port Header</p> <p>1 x TPM Header</p> <p>4 x LED Header (5V)</p> <p>1 x LED Header (12V)</p> <p>* M.2 (E Key) Wi-Fi card is not provided</p> |
| RAID         | <p>Supports RAID 0, 1 for SATA storage devices</p> <p>Supports RAID 0, 1 for M.2 NVMe storage devices</p>   |
| DIMENSION    | Micro ATX Form Factor Dimension: 24.4cm x 24.4cm ( W x L )  |
| OS SUPPORT   | <p>Supports Windows 10(64bit) / Windows 11(64bit)</p> <p>※Biostar reserves the right to add or remove support for any OS with or without notice.</p>  |
| ACCESSORIES  | <p>2 x SATA Cable</p> <p>1 x I/O Shield</p> <p>1 x Cable for WiFi Antenna(Wi-Fi配件為選購，請向當地經銷商購買。)</p>  |

## OVERVIEW

|   |  |
|---|--|
|  | <p><b>AMD B850 chipset</b></p> <p>The AMD B850 platform is the foundation for next-generation gaming and content creation experiences. Featuring enhanced overclocking capabilities, DDR5 memory support with AMD EXPO™ Technology, and PCIe® 5 connectivity for NVME storage, the AMD B850 platform is ready to power your desktop for years to come.</p> |
|  | <p><b>HD Audio</b></p> <p>Provides high quality sound with minimal loss of audio fidelity.</p>   |
|  | <p><b>Hi-Fi Ground</b></p> <p>BIOSTAR Hi-Fi Ground ( Golden Line ) is noise-blocking multi-layer PCB design to isolates analog audio signals from digital sources. Unique PCB layout is ideal for exceptional clarity and high fidelity sound.</p>   |

|   |  |
|---|--|
|     | <h3>DisplayPort</h3> <p>DisplayPort is a digital display interface developed by the Video Electronics Standards Association (VESA). The interface is primarily used to connect a video source to a display device such as a computer monitor, though it can also be used to carry audio.</p>   |
|    | <h3>DX12</h3> <p>DirectX 12 introduces the next version of Direct3D, the graphics API at the heart of DirectX. Direct3D is one of the most critical pieces of a game or game engine, and we've redesigned it to be faster and more efficient than ever before. Direct3D 12 enables richer scenes, more objects, and full utilization of modern GPU hardware.</p> |
|    | <h3>HDMI® 2.1</h3> <p>HDMI® 2.1 supports true 4K resolution- 4096*2160@120hz. A significant increase in bandwidth is up to 18mbps, and significant enhancements are added to support the continued increase consumer demands on video and audio experience.</p>  |
|    | <h3>SATAIII 6Gbps</h3> <p>SATAIII 6Gbps provides a higher bandwidth to retrieve and transfer HD media. With this super speed data transfer, SATAIII allows an incredible data boost which is 2x faster than the SATA II.</p>   |
|   | <h3>DDR5</h3> <p>DDR5 provides 50% higher bandwidth than DDR4, the frequency can be up to 6000+(OC)MHz, and can boasts the largest memory capacity available. It also supports dual channels and has lower power consumption, which can provide better performance and experience for overclockers.</p>  |
|  | <h3>PCIe 5.0</h3> <p>PCIe 5.0 increases the data rate from 16GT/s to 32GT/s, which is twice as fast as PCIe 4.0. The maximum data transfer of bandwidth for two-way communication can reach 128GB/s. In addition, synchronized compatible with PCIe 4.0 and previous versions of devices.</p>  |
|  | <h3>PCIe 4.0</h3> <p>PCIe 4.0 is the ubiquitous and general-purpose PCI Express I/O standard. At 16GT/s bit rate, the interconnect performance bandwidth is doubled over PCIe 3.0, while preserving compatibility with software and mechanical interfaces.</p>   |
|  | <h3>PCIe 4.0 M.2</h3> <p>PCIe 4.0 M.2 delivers the highest bandwidth and lower latency. It is 2 times faster compared with PCIe 3.0 M.2 .</p>  |
|  | <h3>PCIe 5.0 M.2</h3> <p>PCIe 5.0 M.2 is the latest storage interface, it delivers the highest bandwidth and lower latency. It is 2 times faster compared with PCIe 4.0 M.2 .</p>  |

|  |  |
|--|--|
|  <p><b>USB 3.2<br/>TYPE-C</b></p>            | <h3>USB 3.2 Gen2 Type-C</h3> <p>USB 3.2 Gen2 offers up to double the transfer speed of USB 3.2 Gen1 at 10 Gbps that allows for much higher data transfer rates and more efficient data transfer. And the Type-C connector is reversible so it's easier to plug in.</p>   |
|  <p><b>USB 3.2<br/>GEN1 TYPE-A</b></p>      | <h3>USB 3.2 Gen1 Type-A</h3> <p>USB 3.2 Gen1 delivers a compelling performance boosts and can be used to connect multiple devices without worrying about compatibility. It is capable of data transfer speeds up to 5Gbps and backwards compatible with all existing USB products.</p>   |
|  <p><b>USB 3.2<br/>GEN2 TYPE-A</b></p>      | <h3>USB 3.2 Gen2 Type-A</h3> <p>USB 3.2 Gen2 is a new standard called SuperSpeed USB 10Gbps to address increased performance and improve data transmission speed. It is for a max data transfer rate of 10Gbps and creates the best possible connection between your devices.</p>  |
|  <p><b>DR. MOS</b></p>                      | <h3>Dr. MOS</h3> <p>Dr. MOS integrates driver ICs and high-side / low-side MOSFETs into a small package to reduce switching losses that enables superior efficiency and performance at higher switching frequencies.</p>   |
|  <p><b>DIGITAL<br/>PWM</b></p>             | <h3>Digital PWM</h3> <p>Digital PWM controller is with dual-output multiphase that faster transient performance and accurately regulated frequency control. It can be enabled to greatly increase system efficiency.</p>   |
|  <p><b>2.5 GbE<br/>LAN</b></p>            | <h3>2.5 GbE LAN</h3> <p>The 2.5 GbE LAN offers faster transmission speeds compared to traditional 1 GbE LAN and is currently the mainstream transmission speed. It enhances data transmission speeds among devices within a local area network, making it particularly suitable for scenarios requiring large-scale data transfer.</p> |
|  <p><b>SOLID<br/>CAPS</b></p>             | <h3>Super Durable Solid Caps</h3> <p>The best quality solid state capacitors with ultra low ESR design, the Super Durable Solid Caps doubles the lifespan.</p>   |
|  <p><b>IRON SLOT<br/>PROTECTION</b></p>   | <h3>Iron Slot Protection</h3> <p>The exclusive Iron Slot Protection can reinforce PCI-E x16 slots to handle heavier graphics cards, prevent bending, and extend longevity of the slot, making the new-gen RACING Series much more robust.</p>  |
|  <p><b>SUPER DURABLE<br/>INDUCTOR</b></p> | <h3>Super Durable Inductor</h3> <p>Super Durable Inductor brings the benefits of higher current capacity, lower energy loss and better power stability.</p>  |

|   |  |
|---|--|
|     | <h3>Moistureproof PCB</h3> <p>The PCB will be oxidizing easily by damp or absorbed moisture, and ionic migration or CAF (Conductive Anodic Filament) will be generated. Moistureproof PCB meets high density and high reliability requirements for moisture proof.</p>   |
|    | <h3>M.2 Cooling Protection</h3> <p>M.2 heatsink features ultra-high cooling efficiency for protecting the M.2 SSD from thermal problems, extending the M.2 SSD lifespan for long-term usage and stable operation. To top it off, this cooling design makes the performance of certain M.2 (PCI-e 3.0x4) products most efficient even under high-temperature operating.</p>                         |
|    | <h3>ESD Protection</h3> <p>ESD (Electrostatic Discharge) is the major factor to destroy the PC by electrical overstress (EOS) condition. ESD occurred by PC users when touch any devices connect to a PC, which may result in damage to the motherboard or parts. ESD protection is designed to protect the motherboard and equipment from damage by EOS.</p>                                      |
|    | <h3>OC / OV / OH Protection</h3> <p>OC / OV / OH Protection design detects overvoltage conditions and prevents voltage surges from spreading in real time. It also actively cuts off the overvoltage supply to protect your system.</p>  |
|  | <h3>VIVID LED DJ</h3> <p>The VIVID LED DJ has launched a brand-new interface that offers better compatibility with peripheral devices, delivering the best lighting experience to users and allowing them to create a unique personal style.</p>   |
|  | <h3>UEFI BIOS</h3> <p>Unified Extensible Firmware Interface (UEFI) is a brand new framework that provides a revolutionary interface. It is a modern clear and easy-to-use graphical user interface. The UEFI comes with a colorful easy-understand icons lead users into the setup layer directly.</p>   |
|  | <h3>BIO-Flasher</h3> <p>BIO-Flasher is a convenient BIOS update tool. Just launch this tool and put the BIOS on USB pen driver before entering the OS. You can update your BIOS with only a few clicks without preparing an additional floppy disk or other complicated flash utility.</p>   |
|  | <h3>A.I FAN</h3> <p>With A.I FAN users can ensure that their gaming PC can maintain its performance while staying cool. According to different cooling needs and usage scenarios, users can control speed modes. Allows users to have more customizability of fan modes and automatically detects different temperatures to make fan operate at defined speed for optimal cooling performance.</p> |
|  | <h3>LED ROCK ZONE</h3> <p>LED ROCK ZONE comes with the RGB 12V LED header and Digital 5V LED header which offer more colorful lighting options to DIY lovers. Adjusting the color of LED and changing system colors by VIVID LED DJ will make you fully enjoy the process of PC modding developing your personal style.</p>  |

|   |   |
|---|---|
|     | <h3>CPU OPT</h3> <p>BIOSTAR offers one more fan header which is called CPU OPT. Users can use it to connect any kind of water coolers for a liquid cooling system. Keep your computer stable and enjoy your machine at the utmost potential.</p>        |
|    | <h3>BIOSTAR RGB SYNC</h3> <p>BIOSTAR RGB SYNC is designed to create your personalized lighting effects. Let all the RGB peripherals and components sync together.</p>   |
|    | <h3>Debug LED</h3> <p>Debug LED helps you identify any issues going with your board or hardware. When error occurs, the corresponding LED lights will inform you on the status of your board or hardware to shorten the test time effectively.</p>      |
|    | <h3>A.I TP Control</h3> <p>A.I TP Control is designed for overclockers. It provides a user-friendly BIOS environment that overclockers can adjust the temperature setting to keep your PC safe and enjoy extreme overclocking performance.</p>          |
|   | <h3>Smart Update</h3> <p>Biostar Smart Update is a utility that can help users run online update. It can download the drivers for your motherboard from Biostar official website and install them automatically.</p>                                    |
|  | <h3>SMART BIOS UPDATE</h3> <p>The easiest way to update the BIOS is provided. Connect the USB driver to the SMART BIOS USB port to update.</p>  |
|  | <h3>Auto Installer</h3> <p>The Auto Installer is capable of automatically installing the required drivers on Windows OS, providing users with a more intuitive and convenient experience, eliminating the hassle of manually searching for drivers.</p> |
|  | <h3>HDMI®</h3> <p>The terms HDMI® and HDMI® High-Definition Multimedia Interface, and the HDMI® Logo are trademarks or registered trademarks of HDMI® Licensing Administrator, Inc. in the United States and other countries.</p>                       |

**\*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!**